

View Online at <https://aerobasegroup.com/nsn/4720-01-021-1586>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.000 inches

**Minimum Inside Bending Radius:**

5.000 inches

**End Application:**

Tarawa class lha

**Burst Test Pressure:**

8000.0 pounds per square inch single response

**Layer Composition And Location:**

Outer layer molded rubber, synthetic err-100

**Maximum Operating Pressure:**

2000.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and oil resistant

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Special Features:**

Weapon system essential

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Air single response and fuel/oil, hydrocarbon single response and water, fresh single response and water, salt single response

**Specification Data:**

81349-mil-h-24136/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541z0

**Mil-std (military Standard):**

Mil-h-24136 spec.