NSN 4720-01-021-7826

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Between 0.173 inches and 0.203 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-021-7826

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.304 inches and 0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
160.000 inches working
Special Features:
2 dust caps and 3 identification straps

NSN 4720-01-021-7826

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0