Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-022-4446

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.625 inches
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer spirally laid steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.000 inches 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches working
Media For Which Designed:
Hydraulic fluid, water base and fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4720-01-022-4446

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

