NSN 4720-01-022-6016

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-022-6016 **Cross Sectional Shape:** Round **Inside Diameter:** 2.000 inches **Outside Diameter:** 2.656 inches **Quick Disconnect Size:** 2.000 inches 2nd end **End Application:** Tank and pump unit, liquid dispensing, for truck mounting **Connection Style:** Cam or lever (external) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 400.0 pounds per square inch **Layer Composition And Location:** 1st layer woven cotton with interwoven steel wire and 2nd layer woven cotton with interwoven steel wire and outer layer molded rubber, synthetic **Hydrostatic Test Pressure:** 125.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and mildew resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 89.000 inches excluding end fittings Media For Which Designed: Fuel/oil, hydrocarbon single response **Specification Data:** 81349-mil-prf-370 government specification **Specification Or Standard:** 2 type and 6 size

Demilitarization: No

Unit Of Measure:

Shelf Life:

N/a

NSN 4720-01-022-6016

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-370 spec.