Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-022-6016

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Outside Diameter:

2.656 inches

Quick Disconnect Size:

2.000 inches 2nd end

End Application:

Tank and pump unit, liquid dispensing, for truck mounting

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

1st layer woven cotton with interwoven steel wire and 2nd layer woven cotton with interwoven steel wire and outer layer molded rubber, synthetic

Hydrostatic Test Pressure:

125.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

89.000 inches excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-mil-prf-370 government specification

Specification Or Standard:

2 type and 6 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4720-01-022-6016

Nonmetallic Hose Assembly - Page 2 of 2



Fiig: A542a0 Mil-std (military Standard): Mil-prf-370 spec.