Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-022-9973

Cros	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	nt-hand 1st end
Insid	de Diameter:
0.37	5 inches
Tem	npurature Rating:
-40.0	0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outs	side Diameter:
0.62	0 inches
Mini	imum Inside Bending Radius:
3.00	0 inches
Exte	erior Color:
Blac	k
Con	nection Style:
Swiv	vel nut flare 1st end
End	Connection Design:
Strai	ight 1st end
Con	nection Type:
Thre	eaded internal tube 1st end
Feat	tures Provided:
Reu	sable end fittings
Burs	st Test Pressure:
1000	0.0 pounds per square inch
Laye	er Composition And Location:
1st la	ayer braided textile yarn and outer layer braided textile yarn
Мах	imum Operating Pressure:
250.	0 pounds per square inch
Thre	ead Size:
0.56	2 inches 1st end
Seat	t Angle:
37.0	degrees 1st end
Hyd	rostatic Test Pressure:
500.	0 pounds per square inch
Oute	er Covering Environmental Protection:
Mild	ew resistant and oil resistant
Vac	uum In Torr:
50.8	1
Insid	de Surface Condition:
Smo	poth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 125.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon and water single response **Thread Series Designator:** Unf 1st end **Specification Or Standard:** 6 size Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0