NSN 4720-01-023-0307

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-023-0307

Inside Diameter:
Between 0.851 inches and 0.906 inches
Tempurature Rating:
275.0 degrees fahrenheit single response
Outside Diameter:
Between 1.078 inches and 1.140 inches
Minimum Inside Bending Radius:
7.375 inches
Angle Between Rigid Elbow Fittings In Deg:
220.0
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.375 inches 2nd end
Seat Angle:
7.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
MALL STREET, AND S
Measuring Method And Length:

NSN 4720-01-023-0307

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unef 1st end
Specification Data:
96906-ms8001 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A542a0