NSN 4720-01-023-7505

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-023-7505

Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
Between 0.594 inches and 0.656 inches					
Minimum Inside Bending Radius:					
4.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
11000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
2750.0 pounds per square inch					
Thread Size:					
0.500 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
5500.0 pounds per square inch					
Outer Covering Environmental Protection:					
Oil resistant and ozone resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
81.000 inches working					
Media For Which Designed:					
Hydraulic fluid single response					
Thread Series Designator:					
Unf 1st end					

NSN 4720-01-023-7505

Nonmetallic Hose Assembly - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0