NSN 4720-01-025-9434

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-025-9434

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.625 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.921 inches |
| Minimum Inside Bending Radius: |
| 5.500 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 7000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 1750.0 pounds per square inch |
| Thread Size: |
| 0.875 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and mildew resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 49.500 inches |
| |

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water single response

NSN 4720-01-025-9434

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Design | ator: |
|--------|---------------|--------|-------|
| | | | |

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0