

View Online at <https://aerobasegroup.com/nsn/4720-01-026-0039>

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.281 inches and 0.313 inches 2nd end

Outside Diameter:

1.156 inches

Minimum Inside Bending Radius:

5.500 inches

Exterior Color:

Natural

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.188 inches 1st end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.266 inches and 0.276 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

1500.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

750.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Furnished with 2 clamps

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 00624, has indicated their part number contained asbestos. They continue to manufacture the same part number without asbestos material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0