

View Online at <https://aerobasegroup.com/nsn/4720-01-026-0039>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Flange Thickness:**

0.281 inches and 0.313 inches 2nd end

**Outside Diameter:**

1.156 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Exterior Color:**

Natural

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.188 inches 1st end

**Connection Style:**

Plain swivel 2nd end

**Bolt Hole Diameter:**

0.266 inches and 0.276 inches 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

1500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

750.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.750 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Furnished with 2 clamps

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 00624, has indicated their part number contained asbestos. They continue to manufacture the same part number without asbestos material

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0