

View Online at <https://aerobasegroup.com/nsn/4720-01-026-0040>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.343 inches and 0.375 inches 1st end

Outside Diameter:

1.437 inches

Minimum Inside Bending Radius:

8.000 inches

Angle Between Rigid Elbow Fittings In Deg:

34.0

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.375 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.266 inches and 0.276 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

750.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

38.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Furnished with 2 clamps; this item has been reviewed for asbestos material. The sources, cage 00624 and 98441, have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0