

View Online at <https://aerobasegroup.com/nsn/4720-01-026-0040>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.125 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Flange Thickness:**

0.343 inches and 0.375 inches 1st end

**Outside Diameter:**

1.437 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

34.0

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.375 inches 2nd end

**Connection Style:**

Plain swivel 2nd end

**Bolt Hole Diameter:**

0.266 inches and 0.276 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Plain face flange 2nd end

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

750.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

38.750 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Furnished with 2 clamps; this item has been reviewed for asbestos material. The sources, cage 00624 and 98441, have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0