## NSN 4720-01-026-1104

**Cross Sectional Shape:** 

Thread Direction: Right-hand 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-026-1104

Inside Diameter:			
0.375 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.625 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Exterior Color:			
Black			
Quick Disconnect Size:			
0.562 inches 2nd end			
Connection Style:			
Push (internal) 2nd end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded external pipe 1st end			
Burst Test Pressure:			
1600.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided fabric and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
400.0 pounds per square inch			
Thread Size:			
0.250 inches 1st end			
Seat Angle:			
30.0 degrees 1st end			
Hydrostatic Test Pressure:			
800.0 pounds per square inch			
Outer Covering Environmental Protection:			
Oil resistant and ozone resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
34.000 inches			
Media For Which Designed:			
Hydraulic fluid, water base and fuel/oil, hydrocarbon single response			

## NSN 4720-01-026-1104

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:

Nptf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0