NSN 4720-01-026-2943

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-026-2943

| One of Ocean and Observe |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.562 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.797 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.875 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 2500.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant and fire resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 420.000 inches working |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |

Unjf 1st end

NSN 4720-01-026-2943

Nonmetallic Hose Assembly - Page 2 of 2



| Specification Data | Spe | ecifica | ition | Data: |
|--------------------|-----|---------|-------|-------|
|--------------------|-----|---------|-------|-------|

81349-mil-h-83797 government specification

Specification Or Standard:

10 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0