NSN 4720-01-026-2946

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-026-2946

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.688 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Nonskive |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 4500.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Oil resistant and weatherproof and ozone resistant and cold resistant |
| Inside Surface Condition: |
| Smooth |

22.000 inches

Measuring Method And Length:

NSN 4720-01-026-2946

Nonmetallic Hose Assembly - Page 2 of 2



| | Media | For | Which | Design | ned: |
|--|-------|-----|-------|--------|------|
|--|-------|-----|-------|--------|------|

Hydraulic fluid, water base and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0