

View Online at <https://aerobasegroup.com/nsn/4720-01-026-3841>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

0.740 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nonskive

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant and hydraulic solution resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.000 inches

Special Features:

Furnished with one connector and one coupling half quick disconnect

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0