

View Online at <https://aerobasegroup.com/nsn/4720-01-026-6459>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.040 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

6500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

55.000 inches

Special Features:

One end labled, 2-1-1 3/8 tee (24930-183842-1), other end labled 2-1-1a window supply (24930-183842-1), impression stamped 1/16 in.

High characters per gps30-101-3

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unef 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0