NSN 4720-01-028-0346

Cross Sectional Shape:

Round

resistant

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-028-0346

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.891 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
1.062 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Alcohol resistant and corrosion resistant and fuel resistant and heat resistant and hydraulic solution resistant and oil resistant and water

NSN 4720-01-028-0346

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length
36.000 inches working
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0