

View Online at <https://aerobasegroup.com/nsn/4720-01-028-1817>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 190.0 degrees fahrenheit single response

Flange Thickness:

0.360 inches 2nd end

Outside Diameter:

1.780 inches

Minimum Inside Bending Radius:

4.500 inches

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.813 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.813 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.420 inches 2nd end

Flange Width:

2.420 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

1.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

37.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0