NSN 4720-01-028-1817

600.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-028-1817

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 190.0 degrees fahrenheit single response
Flange Thickness:
0.360 inches 2nd end
Outside Diameter:
1.780 inches
Minimum Inside Bending Radius:
4.500 inches
Exterior Color:
Natural
Center To Center Distance Between Bolt Holes Along Width:
1.813 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.813 inches 2nd end
Bolt Hole Quantity:
4 2nd end
Flange Length:
2.420 inches 2nd end
Flange Width:
2.420 inches 2nd end
Connection Style:
Plain swivel 2nd end
Bolt Hole Diameter:
0.266 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Buret Toet Proceuro

NSN 4720-01-028-1817

Nonmetallic Hose Assembly - Page 2 of 2



Layer Composition And Location: Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 1.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 450.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Inside Surface Condition:** Convoluted **Measuring Method And Length:** 37.000 inches working Flange Style: Rectangular (includes square) 2nd end **Thread Series Designator:** Unj 1st end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A542a0