Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-028-1823

# Cross Sectional Shape:

Round

**Thread Class:** 

3b 1st end

## **Thread Direction:**

Right-hand 1st end

## Inside Diameter:

0.750 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

1.250 inches

Minimum Inside Bending Radius:

#### 9.500 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

### **End Connection Design:**

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Reusable end fittings

### Thready Qty Per Inch (tpi):

12 1st end

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

2250.0 pounds per square inch

#### **Thread Size:**

1.062 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

4500.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Oil resistant and ozone resistant and weatherproof

### Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length:

82.000 inches

## Media For Which Designed:

Hydraulic fluid, water base and fuel/oil, hydrocarbon single response

### **Thread Series Designator:**

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A542a0