NSN 4720-01-028-3817

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.406 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-028-3817

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant
Vacuum In Torr:
50.8

NSN 4720-01-028-3817

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
48.000 inches working
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8000 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0