Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-028-5544

Cross Sectional	Shape:
Round	

Thread Class:

2b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.250 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.625 inches

Minimum Inside Bending Radius:

#### 4.000 inches

Exterior Color:

Black

#### Quick Disconnect Size:

0.500 inches 2nd end

## **Connection Style:**

Swivel nut flare 1st end

### End Connection Design:

Straight 2nd end

### Connection Type:

Threaded internal tube 1st end

### **Burst Test Pressure:**

11000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

2750.0 pounds per square inch

#### Thread Size:

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

5500.0 pounds per square inch

### Inside Surface Condition:

Smooth

## Measuring Method And Length:

46.250 inches

### **Special Features:**

Includes plug and chain



Media For Which Designed:

Hydraulic fluid single response

# Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0