NSN 4720-01-029-2743

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-029-2743

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response		
Outside Diameter:		
0.450 inches		
Minimum Inside Bending Radius:		
4.000 inches		
Angle Between Rigid Elbow Fittings In Deg:		
0.0		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Elbow 2nd end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
9000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided steel wire		
Maximum Operating Pressure:		
1500.0 pounds per square inch		
Thread Size:		
0.562 inches 2nd end		
Seat Angle:		
37.0 degrees 2nd end		
Hydrostatic Test Pressure:		
3000.0 pounds per square inch		
Flow Angle:		
90.0 degrees 2nd end		
Outer Covering Environmental Protection:		
Abrasion resistant and corrosion resistant and oil resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
10.750 inches working and 11.000 inches working		

NSN 4720-01-029-2743

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0