NSN 4720-01-029-4194

Cross Sectional Shape:

Inside Surface Condition:

Smooth

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-029-4194

Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.310 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.450 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Exterior Color:			
Natural			
Angle Between Rigid Elbow Fittings In Deg:			
0.0			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Elbow 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.562 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Outer Covering Environmental Protection:			
Abrasion resistant and corrosion resistant and oil resistant			

NSN 4720-01-029-4194

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

32.750 inches working and 33.250 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0