

View Online at <https://aerobasegroup.com/nsn/4720-01-029-7063>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.313 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.446 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

30.875 inches working

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

81349-mil-h-25579c government specification

**Specification Or Standard:**

1 class and 6 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-25579 spec.