Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-030-0599

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.906 inches	
Minimum Inside Bending Radius:	
7.000 inches	
Connection Style:	
Flared 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external tube 1st end	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synt	hetic
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Thread Size:	
0.500 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
63.000 inches	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-030-0599

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

