

View Online at <https://aerobasegroup.com/nsn/4720-01-031-1619>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.880 inches

Temperature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit 1st response

Outside Diameter:

1.110 inches

Minimum Inside Bending Radius:

7.380 inches

Exterior Color:

Natural

Connection Style:

Swivel nut, flareless 1st end

End Fitting Component And Material:

Socket steel comp 304 2nd end

Fitting Component And Surface Treatment:

Socket passivate 2nd end

Connection Type:

Internal quick disconnect 2nd end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2400.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

600.0 pounds per square inch

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

1200.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.600 inches working

Special Features:

External protection type and location- fire shield, silicone rubber coated asbestos braid , inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unj 1st end

Specification Data:

Mil-h-27267 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-27267 spec.