## NSN 4720-01-031-3290

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-031-3290

0.688 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 375.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
3750.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response

## NSN 4720-01-031-3290

Nonmetallic Hose Assembly - Page 2 of 2



Inread Series Designator:
Unf 2nd end
Specification Data:
73030-758981-3 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0