Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-031-3296

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Tempurature Rating:

-67.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.125 inches

Minimum Inside Bending Radius:

7.375 inches

Exterior Color:

Natural

Connection Style:

Flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and salt water resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

51.934 inches and 52.666 inches

NSN 4720-01-031-3296

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unj 1st end

Specification Data:

81349-mil-h-25579 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.