## NSN 4720-01-031-4386

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-031-4386

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end  Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
3.750 inches
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
110.000 inches
Media For Which Designed:
Brake fluid, nonmineral oil single response
Thread Series Designator:
Nptf 1st end
Specification Data:
81349-mil-h-3992 government specification
Specification Or Standard:
1 type and 1 class
Shelf Life:

N/a

## NSN 4720-01-031-4386

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0