NSN 4720-01-032-2415

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-032-2415

| 3b 1st end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.340 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.547 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Socket aluminum alloy 1st end |
| Fitting Component And Surface Treatment: |
| Nipple cadmium all ends |
| Connection Type: |
| Threaded internal tube 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.5625 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |

NSN 4720-01-032-2415

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

12.000 inches excluding end fittings

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

Onch En

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A542a0