## NSN 4720-01-033-2098

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-033-2098

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.530 inches				
Minimum Inside Bending Radius:				
4.000 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Nonskive and reusable end fittings				
Burst Test Pressure:				
11000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
2750.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
5500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

79.000 inches

## NSN 4720-01-033-2098

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed:

Air and grease and fuel/oil, hydrocarbon and water single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0