

View Online at <https://aerobasegroup.com/nsn/4720-01-033-2806>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.266 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

2.250 inches

Hose Or Tubing Specification/std Data:

Mil-h-13444, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1250.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Outer Covering Environmental Protection:

Cold resistant and fuel resistant and mildew resistant and oil resistant and ozone resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.250 inches

Second End Swivel Action Capability:

Not included

Thread Series Designator:

Unf 2nd end

Specification Data:

81349-mil-h-13444 government specification

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.