

View Online at <https://aerobasegroup.com/nsn/4720-01-033-2808>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

1.625 inches

Minimum Inside Bending Radius:

8.000 inches

Hose Or Tubing Specification/std Data:

Sae, j517, 100r4, size 20-81348 standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Sae, j516, size 20-81348 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

800.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided textile yarn err-100 or 1st layer woven fabric err-100

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

1.250 inches 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Gas single response and hydraulic fluid single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0