

View Online at <https://aerobasegroup.com/nsn/4720-01-033-7640>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.860 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response

Outside Diameter:

1.240 inches

Minimum Inside Bending Radius:

9.625 inches

Quick Disconnect Size:

1.500 inches 2nd end

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer spirally laid corrosion resistant steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

30.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources, 00624, 81205, have indicated their part numbers contained asbestos. They continue to manufacture the same part number without asbestos material

Thread Series Designator:

Unj 1st end

Specification Data:

81349-mil-h-38360 government specification

Specification Or Standard:

16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0