

View Online at <https://aerobasegroup.com/nsn/4720-01-033-7861>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

400.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.875 inches 1st end

Flange Thickness:

0.500 inches 2nd end

Outside Diameter:

2.359 inches

Minimum Inside Bending Radius:

13.000 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Angle Between Rigid Elbow Fittings In Deg:

105.0

Bolt Hole Quantity:

4 2nd end

Flange Outside Diameter:

5.000 inches 1st end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.625 inches 2nd end

Raised Face Height:

0.140 inches 1st end

Raised Face Diameter:

2.875 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

Outer layer braided nickel copper alloy wire

Maximum Operating Pressure:

100.0 pounds per square inch

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Measuring Method And Length:

31.500 inches working

Flange Style:

Round w/ bolt holes 2nd end

Special Features:

A 90 degrees elbow is located 16.031 in. From first end and 15.469 in. From second end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0