Nonmetallic Hose Assembly - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-033-8938

Cross Sectional Shape: Round Inside Diameter: 0.312 linches Outside Diameter: 0.375 linches Minimum Inside Bending Radius: 4.000 linches Quick Disconnect Size: 2.100 linches 1st end Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal plunger type 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer Darialed cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: Patient Suitate Condition: Straight Add Ad Length: Hydrostatic Test Pressure: Noch <th></th>	
Inside Diameter: 0.312 inches 0.312 inches 0.375 inches 0.375 inches 0.375 inches 0.300 inches 0	Cross Sectional Shape:
0.312 inches Cutside Diameter: 0.375 inches Cutside Diameter: 0.375 inches Cuto: 0.375 inches Cuto: 0.325 inches Cuto: 0.320 inches Stend Cuto: 0.320 inches Cuto: 0.320 inch	Round
Outside Diameter: 0.375 inches Minimum Inside Bending Radius: 4.000 inches Quick Disconnet Size: 2.100 inches 1st end Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Maximum Operating Pressure: 2000.0 pounds per square inch Maximum Operating Pressure: 2000.0 pounds per square inch Hadrischaft Test Pressure: 2000.0 pounds per square inch Maximum Operating Pressure: 2000.0 pounds per square inch Hordischaft Test Pressure: 2000.0 pounds per square inch Houtiest Hout and oil resistant Holdes Stratae Condition: 110.00 inches Messering Method And Length: 110.00 inches Paraleit, hydrocarbon single response Shell Lite: Na Demilatirzation: Interseriestion: Fueloi Na	Inside Diameter:
0.375 inclusis Minimum Inside Bending Radius: 4.000 inclusis 0.000 inclusis 0.100 inclusis stand Connection Style: Internal plunger type 1st end Fact Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 1000.0 pounds per square inch Burst Concellon: Fuel resistant and oil resistant Inside Surface Condition: Fuel resistant and oil resistant Incole Surface Condition: Incole Surface Condition: Name Heil Fuel Nubrocation single response Surfa If If: <	0.312 inches
Minimu Inside Bending Radius: 4.000 inches Cuick Disconnect Size: 2.100 inches 1st end Connection Siyle: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1 st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Snooth Measuring Method And Length: Interve Mais Could Cordson single response Shelf Life: Na Distilarization: Into Measure: Fuel Not Measure:	Outside Diameter:
4.000 inches Cuick Disconnect Size: 2.100 inches 1st end Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Exper Composition And Location: 1st laver braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2st laver Straigen Strai	0.375 inches
Quick Disconnect Size: 2.100 inches 1st end Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 9000.0 pounds per square inch Hydrostito Test Pressure: 4500.0 pounds per square inch Hydrostito Test Pressure: 4500.0 pounds per square inch Hydrostito Test Pressure: 4500.0 pounds per square inch Duter Covering Environmental Protection: Fuel resistant and oil resistant Indes Surface Condition: Smooth Measuring Method And Length: 11.000 inches Fuel/oil, hydrocarbon single response Shef Life: Na Inof Measure: Inof Measure: Inof Measure: Inof Measure: Image:	Minimum Inside Bending Radius:
2.100 inches 1st end Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Maximum Operating Pressure: 2000.0 pounds per square inch Mutor Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocaton single response Sheff Life: Na Mitor Measure: 	4.000 inches
Connection Style: Internal plunger type 1st end End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Mydrostatic Test Pressure: 2000.0 pounds per square inch Mydrostatic Test Pressure: 15tal ayer Lowering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Media For Which Designed: In Ju0.000 inches Media For Which Designed: Puel/oil, hydrocarbon single response Shell Ife: Na Luit Of Measure: Image:	Quick Disconnect Size:
Internal plunger type 1 st end End Connection Design: Straight 1 st end Connection Type: Internal quick disconnect 1 st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1 st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4000.0 pounds per square inch Muter Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 10.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Sheff Life: Na Mit Of Measure: Pomilitarization: No	2.100 inches 1st end
End Connection Design: Straight 1st end Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 3000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Mutro Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 10.00 inches Media For Which Designed: Fuel/roil, hydrocarbon single response Shelf Life: Na Unit Of Measure: Incomposition Single response Shelf Life: Na Diti Of Measure: Incomposition Single response Shelf Life: Na Diti Of Measure: Image:	Connection Style:
Straight 1st end Conection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 2000.0 pounds per square inch Mut Covering Environmental Protection: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Sheff Life: Na Init of Measure: - - Demilitarization: No	Internal plunger type 1st end
Connection Type: Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Pudrostatic Test Pressure: 4500.0 pounds per square inch Pudrostatic Test Pressure: 4500.0 pounds per square inch Pudrostatic Test Pressure: 4500.0 pounds per square inch Pudre Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Sheff Life: Iva Puniltarization: No Fig:	End Connection Design:
Internal quick disconnect 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Uter Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: Na Int of Measure: No Int of Measure: No Int of Measure:	Straight 1st end
Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Metasuring Method And Length: 110.000 inches Metale For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: Na Dint of Measure: Image: No Fig:	Connection Type:
9000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Metasuring Method And Length: 110.000 inches Piel/Voli, hydrocarbon single response Shelf Life: N/a Intio Of Measure: Intio Method Part Piel/Piel/Piel/Piel/Piel/Piel/Piel/Piel/	Internal quick disconnect 1st end
Layer Composition And Location: 1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 10.000 inches Puel/oil, hydrocarbon single response Shelf Life: N/a Dut of Measure: - Puel/oil, hydrocarbon single response Puel/oil, hydrocarbon single response Na Dut of Measure: - Puel/oil, hydrocarbon single response Fuel/oil, hydrocarbon single response Puel/oil fuel Na Dut of Measure: - Puel/oil fuel No Fig:	Burst Test Pressure:
1st layer braided cotton cord and outer layer braided wire Maximum Operating Pressure: 2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Sheff Life: Na Dut of Measure: - Penilitarization: No Fig:	9000.0 pounds per square inch
Maximum Operating Pressure:2000.0 pounds per square inchHydrostatic Test Pressure:4500.0 pounds per square inchOuter Covering Environmental Protection:Fuel resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:110.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseShelf Life:N/aDemiltarization:~Fuel/oil, fig:	Layer Composition And Location:
2000.0 pounds per square inch Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Demilitarization: No	1st layer braided cotton cord and outer layer braided wire
Hydrostatic Test Pressure: 4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filg:	Maximum Operating Pressure:
4500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Sheff Life: N/a Ditt Of Measure: Demilitarization: No Fig:	2000.0 pounds per square inch
Outer Covering Environmental Protection: Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Hydrostatic Test Pressure:
Fuel resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	4500.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	Outer Covering Environmental Protection:
Smooth Measuring Method And Length: 110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Penilitarization: No Fig:	Fuel resistant and oil resistant
Measuring Method And Length:110.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Inside Surface Condition:
110.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Smooth
Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Measuring Method And Length:
Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	110.000 inches
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which Designed:
N/a Unit Of Measure: Demilitarization: No Fiig:	Fuel/oil, hydrocarbon single response
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A542a0	Fiig:
	A542a0