NSN 4720-01-033-9718



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-033-9718 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.968 inches **Minimum Inside Bending Radius:** 7.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.500 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 7000.0 pounds per square inch

Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:**

Smooth

Measuring Method And Length:

39.000 inches

NSN 4720-01-033-9718

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Two band markers, oneeach end, marked circuit no. 132g
Thread Series Designator:
Unf 2nd end
Specification Or Standard:
B type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0