## NSN 4720-01-034-5032

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-034-5032

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Outside Diameter:
0.968 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
175.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
350.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.750 inches working and 24.250 inches working
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-01-034-5032

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0