NSN 4720-01-035-8433

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-035-8433 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.312 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

5.750 inches working

NSN 4720-01-035-8433

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8000 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0