## NSN 4720-01-037-1710

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-037-1710

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted lare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 40.000.0 pounds per square inch Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 80.00.0 pounds per square inch Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 80.00.0 pounds per square inch Understand Section	One of Continued Observed
Tread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.3640 inches Outside Diameter: 0.3640 inches Minimum Inside Bending Radius: 0.5000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 400.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oli resistant Bisside Surface Condition: Smooth Measuring Method And Length:	
Inside Diameter: 0.375 inches Tompurature Rating: -8.50 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 18to layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Stee: 0.375 inches 1st end Seat Angle: 0.30 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Outer Covering Environmental Protection: Out resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 0.375 inches 1st end Seat Angle: 0.30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch United Size: 0.375 inches 1st end Seat Angle: 0.00.0 pounds per square inch United Size: 1.000.0 pounds per square inch 1.0	
Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Saat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter: 0.840 inches Minimum Inside Bending Radius: 5.000 inches  Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Rousable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Outside Diameter:  0.840 inches  Minimum Inside Bending Radius: 5.000 inches  Exterior Color:  Black  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 1600.0.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Invented flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threadde external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Exterior Color: Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Black Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	
Connection Style: Inverted flare 1st end  End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Exterior Color:
Inverted flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length:	
End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Connection Style:
Straight 1st end  Connection Type: Threaded external pipe 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth  Measuring Method And Length:	Inverted flare 1st end
Connection Type: Threaded external pipe 1st end Features Provided: Reusable end fittings Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	End Connection Design:
Threaded external pipe 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length:	Straight 1st end
Features Provided: Reusable end fittings  Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length:	Connection Type:
Reusable end fittings  Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  8000.0 pounds per square inch  Outer Covering Environmental Protection:  Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	Threaded external pipe 1st end
Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  8000.0 pounds per square inch  Outer Covering Environmental Protection:  Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	Features Provided:
16000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  8000.0 pounds per square inch  Outer Covering Environmental Protection:  Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	Reusable end fittings
Layer Composition And Location:  1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Burst Test Pressure:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	16000.0 pounds per square inch
Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  8000.0 pounds per square inch  Outer Covering Environmental Protection:  Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	Layer Composition And Location:
4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  8000.0 pounds per square inch  Outer Covering Environmental Protection:  Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	Maximum Operating Pressure:
0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length:	4000.0 pounds per square inch
Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Thread Size:
30.0 degrees 1st end  Hydrostatic Test Pressure: 8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth  Measuring Method And Length:	0.375 inches 1st end
Hydrostatic Test Pressure: 8000.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Seat Angle:
8000.0 pounds per square inch  Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	30.0 degrees 1st end
Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Hydrostatic Test Pressure:
Oil resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:	8000.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length:	Outer Covering Environmental Protection:
Smooth  Measuring Method And Length:	Oil resistant
Measuring Method And Length:	Inside Surface Condition:
	Smooth
18.000 inches	Measuring Method And Length:
	18.000 inches

Fuel/oil, hydrocarbon single response

Media For Which Designed:

## NSN 4720-01-037-1710

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0