## NSN 4720-01-037-4322

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-037-4322 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.620 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1200.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 600.0 pounds per square inch **Vacuum In Torr:** 50.8

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

11.000 inches

## NSN 4720-01-037-4322

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ned:

Air and fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0