

View Online at <https://aerobasegroup.com/nsn/4720-01-038-8841>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 190.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 1st end

Minimum Inside Bending Radius:

4.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

2.375 inches 1st end

Flange Width:

2.375 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.266 inches 1st end

Raised Face Height:

0.052 inches 1st end

Raised Face Diameter:

1.938 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Raised face flange 1st end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer fiberglass cloth and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

300.0 pounds per square inch

Hydrostatic Test Pressure:

450.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

35.380 inches working

Flange Style:

Rectangular (includes square) 1st end

Special Features:

Layer composition and location first layer fiberglass cloth outer layer braided corrosion resistant steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0