NSN 4720-01-039-3209

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-039-3209 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.531 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1400.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 350.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 700.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant and fuel resistant and heat resistant and oil resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 18.000 inches **Thread Series Designator:** Unf 1st end

N/a

Shelf Life:

NSN 4720-01-039-3209

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0