## NSN 4720-01-039-8845



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-039-8845 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.310 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.475 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 10500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** 

Smooth **Measuring Method And Length:** 23.125 inches working **Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

## NSN 4720-01-039-8845

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0