Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-0581

0	
	ss Sectional Shape:
Rou	
	ead Class:
	1st end
	ead Direction:
	ht-hand 1st end
	de Diameter:
-	98 inches
	npurature Rating:
-65.	0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Out	side Diameter:
0.47	75 inches
Min	imum Inside Bending Radius:
2.50	00 inches
Cor	nnection Style:
Swi	vel nut, flareless 1st end
Enc	I Connection Design:
Stra	aight 1st end
Cor	nnection Type:
Thre	eaded internal tube 1st end
Fea	tures Provided:
Nut	s drilled for lockwire
Bur	st Test Pressure:
105	00.0 pounds per square inch
Lay	er Composition And Location:
Out	er layer braided corrosion resistant steel wire
Max	kimum Operating Pressure:
300	0.0 pounds per square inch
Thr	ead Size:
0.56	62 inches 1st end
Нус	Irostatic Test Pressure:
600	0.0 pounds per square inch
Insi	de Surface Condition:
Sm	ooth
Mea	asuring Method And Length:
17.6	625 inches working
Thr	ead Series Designator:
Unji	f 1st end
She	elf Life:
N/a	
Uni	t Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

