NSN 4720-01-040-0582

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-0582

Cross Sectional Shape
Cross Sectional Shape:
Round Thread Class
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.475 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
10500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.250 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-040-0582

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0