NSN 4720-01-040-0583



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-040-0583 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.298 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.475 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Nuts drilled for lockwire **Burst Test Pressure:** 10500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 24.750 inches working **Thread Series Designator:** Unjf 1st end Shelf Life: N/a

--

Unit Of Measure:

NSN 4720-01-040-0583

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0